

One of the most important sections of PC PLUS magazine has to be the Help Screen section. Since it first appeared back in Issue 3 it has become a meeting place for raw beginners and hardened hackers alike, generating a never-ending stream of tips and advice, batch files and program listings. It is certainly a valuable source of information for both readers and staff, as more amazing ways of getting that little bit more out of your PC are revealed every month.

This 16-page booklet contains just 27 of these snippets, and provides a foretaste of The Help Screen Collection, a 160-page book containing the very best from the Help Screen and FactSheet sections, sorted, indexed and even re-written where necessary. See the back of this booklet for further details.

We have not credited the author of each original letter, but special thanks go to Jane Toft for designing this booklet, Paul Stephens, Simon Williams and Andy Wilton who wrote many of the replies, Paul Mullen of the Independent PC Users Group who provided much useful information, and of course all the readers who have contributed over the years.

Matt Nicholson

Published by Future Publishing Limited of Bath and distributed free with the January 1990 issue of PC PLUS magazine. Although we have taken great care to ensure that the contents of this booklet are accurate we cannot guarantee that every tip works with every type of PC compatible hardware or software. No part of this publication may be reproduced without permission.

## **Surplus Line Feeds**

A problem that occurs with some word processor and printer combinations is when the software sends a line-feed command along with a carriage return, to make sure that the next line does not overwrite the first, and the printer puts in a line-feed command as well. The result is two line feeds and a surplus blank line between each line of text.

Most printers have a small 'dip' switch, usually round the back or under a flap somewhere (see the manual for details), that determines whether a line feed is added whenever a carriage return is received. If you are having problems change the position of this switch. If this doesn't work then you may be able to stop the line feed from the software. NewWord and WordStar, for example, includes special printer drivers that do not send a line-feed with each carriage return.

A rather more drastic solution is to disable pin 14 of the centronics cable. Earthing pin 14 tells the printer to line-feed after each carriage return, so disabling it can solve the problem. This can be done either by disconnecting the wire from the pin inside the D-connector, or taping over the connectors at the printer end of the lead.

#### All About Batch Files

These are special files, with the file extension BAT, which consist of a series of MS-DOS commands. They are executed by simply entering the file name, without the BAT extension.

There are several ways of writing batch files. Perhaps the simplest is to use the command copy con BATCH. BAT, a special use of the COPY command that copies what ever you type straight into a file called, in this instance, BATCH.BAT. When you have finished, enter 'Control-Z' by holding down [Ctrl] while tapping [Z], and then pressing [enter]. The new file will then be 'copied'.

You can call a batch file anything you like, though it is advisable not to call it by the same name as any other files on the disk with the extension COM or EXE as these have priority. Perhaps the most useful

# Sending Form Feeds

Most printers interpret ASCII code 12 as a 'form feed' command, automatically moving on to the top of a new sheet of paper when it is received. Fortunately this control code can actually be entered from the MS-DOS prompt directly, simply by holding down [Ctrl] and tapping [L]. The following batch file, called FF.BAT, can be useful. Simply enter FF at the

MS-DOS prompt to send a 'form feed' instruction to the printer:

ECHO OFF ECHO ^L >PRN

Displaying this batch file using the MS-DOS command TYPE reveals the ^L to have been replaced by the biological symbol that represents ASCII code 12.

name is AUTOEXEC.BAT, as this performs a unique function in MS-DOS. Any file with this name is AUTOmatically EXECuted every time you turn your PC on, or re-boot by holding down [Ctrl] and [Alt] and simultaneously pressing [Del].

For example: supposing you have used CONFIG.SYS to set up a RAM disk called Drive C, and want to set up a disk to automatically copy the program file PROGRAM.COM into RAM disk, transfer control to the RAM disk, and then run the program. On the way you might also set VERIFY ON so that any file copying is automatically verified. You would do this by entering the following on the A-prompt:

```
A>copy con autoexec.bat
VERIFY ON
COPY program.com c:
c:
program
^Z
```

# Finding Text Across Files

Here are two variations of a simple batch file that takes the same command parameters as the DOS command FIND, but accepts wild cards for the file specification. The first handles badly matched files specifications elegantly, The second is of the quick one-liner variety:

```
Variation One:
ECHO OFF
if exist %2 goto found
ECHO No files match specification
goto end
:found
for %%a in (%2) do find %1 %%a
:end

Variation Two:
if exist %2 for %%a in (%2) do find %1 %%a
```

1 File(s) copied

#### **Typewriter**

An expensive word processor is all very well for writing *War and Peace II – Peace and Quiet*, but it is a bit excessive for writing short memos to your boss reminding him about your imminent rise: it takes longer to load the word processor than it does to write the memo.

What follows is a short batch file that turns your PC and printer into an electronic typewriter. Enter it in a file called TW.BAT and you can summon it by entering **TW**. It has disadvantages, in that it doesn't word-

wrap and you have to get every line right before sending it to the printer – but it's free, so who's complaining?

## **Printing Files**

You can send a file to the printer by first pressing [Ctrl] and [P], which echoes screen display to the printer, and then using the TYPE command. [Ctrl [P] is a toggle, so press it again to stop echoing to the printer.

However a better way is COPY filename PRN. The PRN part of this command is a special MS-DOS 'reserved file name' which means the currently selected printer. You won't see the file's contents displayed on the screen, and your print won't contain any surplus A-prompts.

## **Using Amstrad's Joystick**

The Amstrad PC1512 and 1640 joystick – the one that plugs into the back of the keyboard – is not compatible with the standard IBM joystick. There is a way round this though, which works with many PC games and relies on the fact that moving the Amstrad joystick control is

## **Fancy Prompts**

The famous A-prompt performs a function, it must be admitted. It tells you that you are logged on to Disk Drive A, but that's about all. But you can tailor the prompt to do a lot more than that – to tell you the time, which sub-directory you are logged in to, and a variety of other information. Below is a handy prompt that you might like to include in your AUTOEXEC.BAT, or put into a separate batch file labelled NEWPRMPT.BAT; but it requires ANSI.SYS to be loaded.

NEWPRMPT.BAT should be entered as a single line. Note that there are three spaces

between the \$d and \$t, and three between \$t and \$p.

Once you've created this batch file enter NEWPRMPT and stand back in amazement. Try pressing [F1] too...

```
CAGING HE 15.99 12426883 611 CONNENDED CONTEXTS

CAGING UNION CONTEXTS

Volume in drive C has no label
Volume Serial Norther in 3842-1703

Directory of CNHEDPSOLVEXT

CHOICE TXY BLOCK
SHORT MAC MORRISC TXT SHORT TXT MILURAPHPI
THEP-13 BNN CHEP1-3 TXT CHEP4-7
CHOP2-18 BNK
TO PHOTO STATE CHEP4-7

16 Pile(s) 39422944 bytes free
```

 equivalent to pressing the cursor keys on the keyboard.

Instead of selecting for 'joystick' at the opening screen of the game, select 'keyboard'. If you are lucky you will be given the option of defining your own keys, in which case you simply move the joystick in the appropriate direction rather than select keys from the keyboard.

## **Batch File Menu System**

It is perfectly feasible to create a menu system using just the MS-DOS batch system. First of all, create a batch file called MENU.BAT which contains the following:

CLS

ECHO 1) Wordstar

ECHO 2) Supercalc

ECHO 3) Chit-Chat

For each choice on the menu, create further batch files as 1.BAT, 2.BAT and 3.BAT. The batch file for 1.BAT might look something like:

cd words

WS

cd \

menu

On running MENU.BAT the screen clears and the menu is displayed. The drive prompt appears at the end of the menu, at which point you simply enter the desired number which then runs the required menu selection. The main menu reappears when you quit the application. Put the command menu at the end of your AUTOEXEC.BAT file and you will automatically be presented with the menu as soon as you turn on or reboot your PC.

The main disadvantage of this system is that it is rather slow as it is continually loading batch files off disk. Each batch file takes up disk space too, which could cause problems on a floppy disk-based system. One way of speeding up at least the initial menu display is to put the menu text into a text file, called say MENU.TXT, and then put the line type menu.txt at the end of AUTOEXEC.BAT. This would have much the same effect but the TYPE command is rather quicker than ECHOing successive lines of text.

An alternative is to use a short utility that returns an errorlevel to the batch file which depends on the key that has been pressed. The advantage of this technique is that the whole menu system can be built up from one batch file, and COM files are considerably faster to execute than batch files.

CHOICE.COM is such a utility that can be generated using DEBUG. Full details on how to create CHOICE.COM for yourself are to be found in the *PC PLUS Help Screen Collection*. See the back of this booklet for further details.

## Amstrad PC1512 Bug

The NVR program has bug in it – if you set the 'extended flow control' to ON, the ramdrive can be changed from C to D or E (assuming a single or twin floppy-drive model). This causes problems with some software, like GEM, which uses the RAM disk. Fortunately setting the flow control back to OFF resets the RAM disk to C.

#### **Printing a Spreadsheet**

Successfully printing a wide spreadsheet on standard-width paper is one of the great challenges of PC computing. The following suggestions apply to a Lotus 1-2-3 compatible spreadsheet and an Epson FX dot matrix or compatible printer. Whichever combination you have, resign yourself to a little experimentation before you get usable results:

- 1. It is best to start by just having a go and see what you get. Enter /PPO to summon the Printer Options menu. This is where you control much of the appearance on the page, but for now simply press [h] to select Header and enter the line of text you want to appear on the top of each page.
- 2. Press [Esc] to move up to the previous menu, and press [r] to define the range (some compatibles may expect the command /PPR to select Printer Range). The top window may show something like Range to Print [Wide 0:Pages 0]: B2.
- 3. Specify the range you want printed, for example A1..M27.
- 4. Select Range again, and this time something like

Range to Print [Wide 124:Pages 1]: A1..M27 may appear. This informs you that the range you have selected is 124 columns wide and one page deep.

**5.** Press [Return] to accept, and select 'Go' from the PrintTo Printer menu.

What you get depends on the printer, but with a reasonably Epson compatible model you should get a respectable result, but probably over several sheets of paper. Go back to the PrintTo Printer Options menu and note that the Left and Right Margins are set to zero and 80 respectively, while Pglines (the number of lines on a page) is set to 66. Most compatibles are quite intelligent when it comes to printers, and are able to work out that they will never get 124 columns on a sheet with margins set at 80, so print the last 44 on a separate sheet.

The Print menu of a typical Lotus 1-2-3 compatible spreadsheet. Getting the settings right for your particular printer is rarely easy

	A	Z III	۲ C	28
PRINTTO PRINTER	100 m	Jan	Feb	All Sales
OPTIONS	& Pickle	800	800	
	- Tomato	1888	1000	
Margins				
Setup	& Pickle	560.80	560.00	
PgLines	Tonato	980.68	900.00	
Header				
Footer	COSTS:			
Type	bread	63.36	63.36	
Quit		36.88	36.88	
	-r cheese			
Branston pickle				
III Cook	ed Ham	.66.67	66.67	

It would be possible to get more on one page if you set the printer to a condensed type face. This is usually done by sending the printer the appropriate ASCII codes first, usually detailed in your printer manual. On the Epson FX it is either ASCII code 15 or ASCII code 27 (frequently called ESC) followed by 15. Fortunately many Lotus compatibles provide for printer Setup codes, so proceed as follows:

- 1. Enter /PPO to get to the printer options menu, and press [s] for Setup.
- 2. Enter \027\015 as the setup code. The slash indicates an ASCII code rather than the actual characters zero, two and seven.
- 3. This puts the printer into condensed mode, however the right margin is still set to 80 characters. On an Epson printer normal character pitch is 10/inch while condensed packs 17/inch. This means that we can get 80\*17/10, or 136 characters across the page quite enough to fit in our spreadsheet. So press [M] to select Margins, [R] to select Right, and enter 136.
- **4.** Press [Esc], check that the range is as previously set, and press [g] to try again!

If you are lucky, and your printer is reasonably Epson-compatible, you should get something quite usable. If not, you will have to try again. See the panel below which describes some of the more common problems and ways of getting round them.

## Typical Spreadsheet Printing Problems

#### **LINES WRAPPING ROUND**

Usually means the margins are set incorrectly on the /PPO menu. Make sure Left Margin is set to zero and Right Margin to the number of characters that fit across the page. You can find this either by multiplying the specified character pitch by the width of the page in inches, or simply counting characters.

#### **INCORRECT PAGE LENGTH**

- 1. The number of lines on a page is specified on the /PPO menu under PgLines. Default is 66, which is suitable for a line pitch of 6 on standard 11-inch paper. You can find out the line pitch either from your printer manual or by measuring off an inch and counting.
- 2. If the printer has a DIP switch controlling

- 'Skip perforation' make sure this is set OFF. Set ON it automatically advances four lines at the end of each page.
- 3. Make sure any DIP switch on the printer controlling 'Page length' is set correctly.

#### SUPERFLUOUS LINES

Most spreadsheets send a carriage return command with line feeds. Make sure any DIP switch on the printer controlling 'automatic line feed' is set OFF.

#### INCORRECT TYPEFACE

Check the DIP switches to make sure the printer is set in Draft mode and not NLQ. Recheck the control codes required to select a condensed typeface.

## **Write Protecting Files**

It is often a good idea to write-protect essential MS-DOS files like AUTOEXEC.BAT, CONFIG.SYS and COMMAND.COM, particularly as some software installation routines insist on altering your configuration files without telling you. These three files will usually be found in the root directory (although it is possible for them to live in another directory). To write-protect them use the commands:

attrib +r autoexec.bat
attrib +r config.sys
attrib +r command.com

If you do later need to modify any of these files you can remove the read-only attribute with ATTRIB -R filename.

#### **Running MS-DOS from WordStar**

As owners of *WordStar* know, the command ^KF takes you out to an MS-DOS prompt from which you can run an MS-DOS command. It is not a proper MS-DOS shell as once the command has executed you must return to *WordStar*. However, if you enter command at the prompt the command processor will be loaded and you can carry on for as long as you wish, entering exit to return to *WordStar*. Do remember though that the command processor takes up memory space of its own so this may not always work.

#### **Hard Carriage Returns**


A little tip for all users of *NewWord 3* and *WordStar 4* who have been bugged by those hard carriage returns that appear at the end of ASCII files when you load them. Try keying [Ctrl] [n] and you will find then magically transformed to the soft carriage return we all know and love. Some versions of *WordStar* can be configured to support this feature

from WSCHANGE; some versions use [Ctrl] [6] instead. Further information is provided in the *PC PLUS Help Screen Collection* (see the back of this booklet for details).

# **Updating Backup Disks**

Although one should of course keep one's hard disk fully backed up at all times, for many of us our day-to-day work only involves changes to a few files in a single sub-directory, so a full backup seems like overkill. It is easier to simply keep up-to-date copies of the files that have changed on a floppy disk.

One problem with editing an ASCII text file in WordStar is the latter's insistence on putting a hard carriage return, shown as a '<', at the end of every line



Unfortunately it is not always that easy to remember which files you have changed through the day. The following batch file, UPDATE.BAT, uses the MS-DOS utility REPLACE to automate the process (which must be on the current path):

ECHO OFF for %%p in ("%1" "%2") do if %%p=="" goto wrong for %%f in (a d) do replace %1\*.\* %2 /%%f/p goto end :wrong ECHO. ECHO Format for the command is ECHO UPDATE source-disk: dest-disk: ECHO as in UPDATE a: c: ECHO Copies files to the back up disk that are either ECHO not already present or are later versions of ECHO those already there. Asks for confirmation before ECHO copying each file. Current directories are ECHO used unless otherwise specified. :end

Note that this technique relies on the internal clock being set correctly. Check with the DATE command.

#### **Umlauts in Microsoft Word**

You can use the macro facility of Microsoft *Word* (at least in version 4) to generate a ü (umlaut) as follows:

- 1 Press [Shift][F3] to begin recording the macro:
- 2 Hold down [Alt] and type the number 129 on the numeric keypad, to enter the code for ü:
- 3 Press [Shift][F3] again to finish recording the macro:
- $4-\mbox{Type uml}\mbox{\sc followed}$  by [Ctrl][u] and [Return], to save the macro to the glossary.

Note that in step 4, the ^ refers to the caret key, usually [Shift][6]. The ü is now saved in the glossary under uml but can also be generated by simply typing [Ctrl][u].

#### **Sending Messages on Prestel**

Electronic mail has been a weakness of Prestel when compared to a scrolling system such as Telecom Gold. On Telecom Gold you can 'upload' a text file of virtually any length to your mailbox and let the Gold computers take care of word wrap and other formatting features. On

Prestel the mailbox will only take one screen-full of text at a time.

However, a little time spent with a decent word processor should enable you to create a file that can be uploaded successfully. You will have to set the line length (or right margin) to automatically word wrap on a 39-character line, and you will have to make sure that the file does not contain more lines than one Prestel screen. It is possible to send more than one screen's worth of text, providing you send a # symbol at the end of each screen — some experimentation will doubtless be necessary!

#### **Selective Delete**

The batch file in the panel below, called DELB.BAT, deletes all the files in a directory except those specified. It is used in the following format and allows as many files to be specified as you wish:

DELB file1 file2 file3...

If any of the files specified do not exist the batch file will echo the filename to the screen, leaving the user to continue by pressing any key or abort by pressing [Ctrl] [c].

## **Counting Disk Drives**

There are a couple of useful little routines used by the installation batch files of a 1512 to provide information about the machine which could be useful in any batch files. On Disk 2 (the blue GEM startup disk) in the directory \Understand \und

The 1640 comes with a routine called DISPCHK.COM (in the

```
Echo off
                                  pause
IF "%1" =="" GOTO fin
                                  GOTO return
MD DELB
                                  :endprog
                                  CD DELB
:begin
IF "%1" =="" GOTO endprog
                                  DIR
IF NOT EXIST %1 GOTO notexist
                                  CD ..
CD DELB
                                  DEL * .*
COPY ..\%1 >NUL
                                  CD DELB
CD ..
                                  COPY *.* .. >NUL
                                  DEL * .*
:return
SHIFT
                                  CD ..
GOTO begin
                                  RD DELB
:notexist
                                  ECHO Deletion Complete!
ECHO %1 does not exist.
                                  :fin
```

10

\GEMSTART directory of Disk 1) which returns the display mode selected by the dip switches. It is used by the AUTOEXEC.BAT file in Disk 1's root directory.

#### **Directory Shorthand**

If you do a DIR of a hard disk sub-directory you will find the following two entries at the very top. The first, the single stop, represents the current directory while the second, the double stop, represents the parent directory, which is the one above the current directory on the directory tree:

Volume in drive C has no label Directory of C:\NW\EMPTY

<DIR> 25-08-88 3:18p
. <DIR> 25-08-88 3:18p

The double dot is commonly used with the Change Directory command, as in CD... but less well known is that these directory entries can be used in other ways too:

copy . b: copies all the files in the current directory on to the floppy disk in drive B:

del . deletes all the files in the current directory;

dir . . shows a list of files in the parent directory.

In much the same way, the backslash \ indicates the root directory, so del\ is equivalent to del\\*.\*.

#### Better Cursor For Your Portable

The Amstrad PPC512 and PPC640 portable, and indeed many laptop machines that use an LCD screen, suffer from a totally inadequate cursor. However you can use the following procedure to turn the cursor into a large flashing block which is rather easier to make out.

First, create a text file called BLOCK.TXT containing the lines:

n block.com a 100 mov ah,1 mov cx,10C int 10 int 20 [return] r cx 9 w

Remember to leave a blank line after int 20 by simply pressing [return]. Now enter DEBUG < block.txt. This creates a tiny file called BLOCK.COM which, when run, changes the cursor to a flashing block. Unfortunately some programs turn the cursor back into a line, but many leave it as a block making it rather easy to see!

#### **Fatal stack errors**

Certain programs sometimes give a 'Fatal Stack Error' or similar message, usually after you have done a couple of hours work and then try to save it to disk! As the message implies the error is fatal and there is nothing you can do except re-boot the machine.

This message is not usually caused by bugs in the software being run: it occurs because Microsoft decided to save a bit of memory when writing MS-DOS version 3.2 by cutting down on the stack space reserved. The solution is to add an additional line to your CONFIG.SYS file which says stacks=64,128. This un-documented command restores the stack space to the value used in earlier versions of DOS.

Even so you can still eventually generate the error on some Amstrad PC1512s (but not for some odd reason on all of them) by turning the volume control down to zero and leaving a book on the keyboard so that it depresses a key.

#### Checking machine configuration

You can check the current status of a printer (if any), and find out (roughly) what display adapter is fitted from within your programs by using MS-DOS interrupt calls. Interrupts are a means of 'low-level' communication between a program and the operating system, and they're normally used by programmers working in assembly language. *QuickBASIC* gives you access to interrupts with the INT86 command, described in the manual. Most other high-level languages provide some means of access.

An interrupt works by accepting parameter data in the 8086 processor's registers, performing whatever tasks are required, then returning replies in these same registers. *QuickBASIC* doesn't give you direct access to the processor registers but instead accepts two arrays of integers, one representing the data you want placed in the registers before the interrupt and the other the reply values returned by MS-DOS.

Two values determine which MS-DOS function is performed; the interrupt number, and the value set in the AH register (i.e. the most significant eight bits of element zero of the input array in *QuickBASIC*).

To check the printer status set AH to 02 and call Interrupt 17 (Hex). The bits of the byte returned in AH have the following meaning when set on:

- 7 Printer busy
- 6 Printer acknowledge
- 5 Out of paper
- Printer on-line
- 3 Printer not connected/unavailable
- Printer timed out

Checking the display adapter is slightly more complex. First, call

interrupt 10 Hex with AH = 12 Hex and BL = 10 Hex. If BL is still equal to 10 Hex on return, then you don't have an EGA adapter fitted.

Next, call interrupt 10 Hex with AH = 0F Hex. On return, AH contains the width of the screen in columns (40 or 80), and AL the screen display mode. If this value is seven, and you don't have an EGA fitted, then you have a monochrome display adapter fitted; if it's not seven, then you have a CGA adapter.

On the PC1512 there's no way of telling whether the monitor fitted is colour or monochrome as both types use exactly the same CGA-emulation mode. You can however check whether your program is running on a 1512 by using a special function which on the 1512 returns the version number of the ROM, but to an IBM PC looks like an illegal cassette interrupt. Call interrupt 15 Hex with AH = 06 Hex. If Carry is set it is not a 1512.

As a further check (This might after all be a legal call on some other clones), load BX with zero beforehand: a 1512 will return BX with the version number, a clone would probably leave it containing zero.

## **Enough Buffers**

Many people are not aware of the influence the BUFFERS parameter in the CONFIG.SYS file has over processing speed. With this in mind one of our readers (C.J. Drouin) set up a series of tests, based mainly on file copying, each time altering the BUFFERS parameter. This produced the following results:

BUFFERS=1	24.11 seconds
BUFFERS=5	13.90 seconds
BUFFERS=10	11.54 seconds
BUFFERS=20	9.39 seconds

## Checking the Directory Path

One problem which can occur when using the MS-DOS commands BACKUP and RESTORE is that DIRectory listings of the backup floppies don't tell you which subdirectories the files originally came from. This is particularly confusing when you have files with the same name in different directories – for example the two files \LIVE\PAYROLL.BAS and \TESTING\PAYROLL.BAS would appear as PAYROLL.BAS and PAYROLL.@@1 on the backup floppy disk's directory.

You can, however, find out the full pathname of a file on a BACKUP floppy disk by using the MS-DOS utility DEBUG. Say you have a file PAYROLL.BAS on a backup floppy in drive A, type debug a:payroll.bas. You should see a - prompt appear. Now enter d and a block of numbers and letters will appear. Somewhere in the top right hand part of this display the full directory and file pathname will be clearly visible. To leave DEBUG just enter q.

Anything above **BUFFERS=20** yields little difference in the processing time, but with each buffer only taking up 0.5k of memory the trade off is well worth it.

#### **Patching QuickBASIC**

Microsoft's *QuickBASIC 2.01* is not fully compatible with the Amstrad PC1512 keyboard when it comes to  $[\mathfrak{L}]$  and  $[\mathfrak{Q}]$ , but can be made so by making the following changes:

Location	old QB.EXE	new QB.EXE	
0002 A176	40h	22h	
0002 A17A	23h	9Ch	
0002 A241	60h	23h	
0002 A252	22h	40h	

Addresses are those found using *PC Tools*. Remember that DEBUG loads files by default from offset address 0100h. Make a backup before you start and use the backup to test the changes.

Hexade	cimal place				Conversion	
5th	4th	3rd	2nd	1st	Hex	Binary
0	0	0	0	0	0	0000
65,536	4,096	256	16	1	1	0001
131,072	8,192	512	32	2	2	0010
196,608	12,288	768	48	3	3	0011
262,144	16,384	1,024	64	4	4	0100
327,680	20,480	1,280	80	5	5	0101
393,216	24,576	1,536	96	6	6	0110
458,752	28,672	1,792	112	7	7	0111
524,288	32,768	2,048	128	8	8	1000
589,824	36,864	2,304	144	9	9	100
655,360	40,960	2,560	160	10	Α	1010
720,896	45,056	2,816	176	11	В	101
786,432	49,152	3,072	192	12	С	1100
851,968	53,248	3,328	208	13	D	110
917,504	57,344	3,584	224	14	Е	1110
983,040	61,440	3,840	240	15	F	1111

This table is particularly useful for converting large hexadecimal numbers to decimal or binary. The first five columns give the decimal equivalent of each place in the hexadecimal number so, for example, the hex number FC8A converts to 61,440+3,072+128+10 = 64,650 in decimal, or 1111 1100 1000 1010 in binary.

14 pages that will increase your PC productivity

# THE HELP SCREEN COLLECTION


The Essential Guide to PC Compatible Hardware and Software

A compilation put together by Matt Nichorson, Jaunch Folio of PC PLUS, and based on the popular Hs-p Screen and FactSheet sections of the magazine, from itsue 3 to the present day. Every from the been re-willful and updated where necessary and frue is a comprehensive index to ensure information is at your fingertips when you need it.

#### Too pages of simple solutions to everyday problems

- Minipuls explains one of MS DOS, hard disks, displicy artiputers and many other aspects of your compacts work
- Handy lookup tables for ASCII and Epson printer codes
- The full source code of many useful utilities you can create for yourself or run directly from the accompanying disk.
- How to make your hard disk run faster.
- How to customise your application's print drivers.
- How to get pound signs on paper and screen.
- Tips on transferring files from a BBC, Apricot, QL or PCW.
- How to get the ESC character into a text file.
- And much, much more!

The Help Screen Collection is available mail order only for £9.95, or £12.95 complete with a disk containing programs and batch files taken from the book. Order from Future Publishing Limited, The Old Barn, Somerton, Somerset TA11 7BR (phone 0458 74011), or by using the card inside this booklet.



Edited by Matt Nicholson